

**PETROGULF MARINE WIRE ROPE GREASE**

**PRODUCT DESCRIPTION**

Petrogulf Marine Wire Rope Grease is produced to protect against wear, rust and to resist and displace water. This tough oil film gives a high load wear protection in adverse operating and weather conditions. It is formulated with an asphaltic base and diluted with a solvent for easy application. It is designed to effectively lubricate when subjected to heavy loads in dirty environment. The carrier film evaporates leaving a tenacious dry wax film that minimizes the collection of abrasive dust and airborne contaminants.

**FEATURES & BENEFITS**

- Easy application
- Long lasting film that eliminates the need to frequent application
- Excellent corrosion protection
- Excellent protection from abrasive dust

**TECHNICAL SPECIFICATIONS**

Petrogulf Wire Rope Grease		
Grade		NLGI 0
Test Parameters	ASTM Method	Typical Values
Thickener type	-	Lithium
Color	Visual	As per requirement
Drop Point, °C	ASTM D566	170
Worked penetration, 25 °C / 60 Strokes	ASTM D217	355-385
Base Oil Viscosity@100°C	ASTN D445	Min 13
Weld load,min, kg	IP 239	Min 180
Timken Ok Load, kg	ASTM D 2509	Min 15
Copper Corrosion	ASTM D4048	Max 1B

**HANDLING, HEALTH, & SAFETY**

- ❖ Lubricant consisting of highly refined mineral oils with specific additives under normal conditions of use, presents no particular toxic hazard. All lubricants of any kind should be handled with great care, particularly avoiding any contact with skin.
- ❖ Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil properly; don't pour down drains, into watercourses or the soil.
- ❖ Take used oil to an authorized collection point.